

Landline™ 16

ON-SURFACE TURBONET™ FLOW

Applications

- On-surface installation
- Shrubs, flower beds and vegetable gardens
- Under mulch
- For flat irrigation zones
- Narrow planting areas

Specifications

- Dripper flow rates:
1.6, 2.1 & 4.2 l/h
(nominal flow rate at 1.0 bar pressure)
- Maximum operation pressure: 4 bar
- Recommended filtration: 120 mesh
- Dripperline OD (outside diameter):
16.0 mm
- Dripperline ID (inside diameter):
13.7 mm

Features and Advantages

- Large, efficient TurboNet™ flow path
- Easy installation
- Tubing flexibility adapts to any shape of planting area
- UV-resistant dripperline
- Long lasting reliability and durability





















Landline™ 16 • O.D. 16.0 mm • Inlet pressure: 3.0 bar • Max. lateral length* (m) / spacing between drippers (m)

Flow rate (l/h)	0.3	0.4	0.5	1.00
1.6	77	96	114	187
2.1	65	81	96	157
4.2	41	52	61	100

*Minimum pressure considered = 0.5 bar , calculated in a plain area

Product	O.D. (mm)	Wall thickness (mm)	Flow rate (l/h)	Spacing (m)	Color	Coil length (m)
Landline™ 16	16	1.2	1.6	0.3	brown	25
			2.1	0.4	dark brown	50
			4.2	0.5		100
				1.0		400

One data from each column is required to achieve a complete catalog description, e.g. Landline™ 16, 16 mm, 1.2 mm, 2.1 l/h, 0.4 m, dark brown, 400 m coil.

	Stabilizer 32000-006500		3/4" x barb male T adapter 32500-011800
	Stabilizer Ø 4 mm galvanized 32000-001600		3/4" x barb male "Y" adapter 32500-011200
	Barbed coupling 32500-010700		3/4" x barb female T adapter 32500-011900
	Barbed T 32500-011300		Shut-off valve 1/2" x barb 76220-008200
	Barbed elbow 32500-012500		Shut-off valve 3/4" x barb 76220-008500
	Barbed cross 32500-006300		Shut-off valve ins x barb 76220-008700
	1/2" x barb male adapter 32500-010900		Rapid start for PE barb (Fits 8 mm hole) 32500-013750
	3/4" x barb male adapter 32500-011000		Rapid start w/ seal x barb for PVC 32500-013770
	3/4" x barb male elbow adapter 32500-012800		Line end 32500-013100

